VISIBLE EMISSION NOTATIONS				
Inspector: Jaime N Gara	Va			
Date of Inspection: 10///15				
Shift: 1st shift or 2nd Shift	t Time:	5ph		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments	
Visible Emission From Shaker	Non	Promote Comments of the Commen		
Visible Emission From Discharge Conveyor System	Non			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS			-		
Inspector: Reden UK	oland III				
Date of Inspection:	2015				
Shift: 1st Shift or 2nd Shift	Time:	5:00am			
hering levelsUnit	Visual 45 46 6		CONTRACTOR OF THE STATE OF THE	nments	
	NORMAL For		in Carlo Section Con Mile Configuration of The Con Configuration of Section Con The Configuration of Section Configuration (Configuration Configuration Conf		State of the second of the second SAM reasons along the second SAM reasons are second second second second
	<u>ABNORMAL</u>				
Visible Emission From Shaker	Normal		·		
Visible Emission From Discharge	i				
Conveyor System	Normal				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector: A CONDINATION ACC	renduc			
Date of Inspection:	5			
Shift: 1st Shift or 2nd Shift	Time:	5:00 am		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		nments	
Visible Emission From Shaker	Normal			
Visible Emission From Discharge Conveyor System	Normal			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector: Jaime N Gara				
Date of Inspection: 10/0/15				
Shift: 1st Shift or 2nd Shift	t Time:	5pm		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		omments :	
Visible Emission From Shaker	Non			
Visible Emission From Discharge				
Conveyor System	NOR			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



Visible Emission From Shaker

Conveyor System

Visible Emission From Discharge





D.1.12 SDS I Daily Visible Emissions Notations Per Each Daylight Shift (Stack SDS 04)

VISIBLE EMISSION NOTATIONS	
Inspector: Public Moland Tit	
Date of Inspection: 10 3 2615	
Shift: 1st Shift 2nd Shift Time: 5:00 am	
Visual de la companya	Gommenisa Propinsi Pr
NORMAL ()	
ABNORMAL	

)armal

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS			<u> </u>		
Inspector: George A. Sorock					
Date of Inspection: 0/8/15	-				
Shift: 1st Shift or 2nd Shift	Time:	5:00 pm			
	Inspections Normal or ABNORMAL			omments.	
Visible Emission From Shaker	Nor				
Visible Emission From Discharge Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



Conveyor System





D.1.12 SDS I Daily Visible Emissions Notations Per Each Daylight Shift (Stack SDS 04)

VISIBLE EMISSION NOTATIONS

nor

Inspector: Smc Ko				
Date of Inspection: Oct 4,15				
Shift: 1st Shift or 2nd Shift	t Time:	5Am		
countries to the entry Unit Estation to the estate of the	Inspection		在1000 PS (1000 PS 1000 PS 100	
	<u>NORMAL</u>			
	or <u>ABNORMAL</u>			
Visible Emission From Shaker	non	1		
Visible Emission From Discharge		·		

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.








VISIBLE EMISSIO	N NOTATIONS	
Inspector:		
Greome	· A Jancher	
Date of Inspection:	16/11/15	

: 1st Shift or 2nd Shift Time: 5=60pm

•	//			
the new or services a minimum of the contract	all the contract the second of the second of the second of	Section 1991	ents as a later to a second and	
		er e		
TANKETER TANKET TO A TO				
新規 MEDINORIVIAL SAR	新华级美国美国大学院建筑工作的创新的市场	。 第25章 1955年 (1954年) 195545 (Account the property of the pr	用的图片的图片的图片的图片的图片图片
2 2				
War				
2				
Wor	•			
	in his Visuali di dic	ABNORMAL TO THE STATE OF THE ST	Inspection. NorMAL Or ABNORMAL	Inspection. NorMal or ABNORMAL

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.





VISIBLE EMISSION NOTATIONS			_		
Inspector: Sme VO					·
Date of Inspection: 0 ct 5	7				
Shift: 1st Shift or 2nd Shift) Time:	9AM			
	Visual 35 4 4 6 Inspections 253		Col	a de la companya de	
and the Control of th	NORMAL :				
	<u>ABNORMAL</u>				
Visible Emission From Shaker	nop	, estimate _e ,			
Visible Emission From Discharge	A . A				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Conveyor System







VISIBLE EMISSION NOTATIONS Inspector: Date of Inspection: // Ist Shift Time: Shift: Unit Visual Comments Inspection NORMAL or **ABNORMAL** Visible Emission From Shaker Visible Emission From Discharge Conveyor System

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS

Inspector:	dand III				
Date of Inspection: U-U-S	XU15	5 m2m			·
Shift: 1st Shift or Znd Shift	t Time:				
Actor in the control of the control	Visual IIII	andratic since open de la come. Comestat l'ambient de la come	Golden and American	nments - 17 - 17 - 18 - 18 - 18 - 18 - 18 - 18	
	<u>NØRMAL</u>	Constantine de la la constantine de la La constantine de la	er foreste er en		enna mesperatura appropriation de la companya de l La companya de la co
	or <u>ABNORMAL</u>				
Visible Emission From Shaker	Normal				
Visible Emission From Discharge	1 /0 0000				
Conveyor System	NOVIVAL				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS					
Inspector: Jaime N Gar	Ya				
Date of Inspection: 196/15					
Shift: 1st Shift or 2nd Shift	Time: 2	5Pm			
# ####################################	Visual parents Inspections		rs. The market product of the Comm	ents: 4 miles 1,5 miles	ere per la companya de la companya d
	<u>NORMAL</u>	tee Same Comment of the Comment of t			
	ot <u>ABNORMAL</u>				
Visible Emission From Shaker	Noa				
Visible Emission From Discharge	` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` ` `				
Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EIVISSION INCITATION		
Inspector: Rube	n Molarolis	
Date of Inspection:	15	
Shift: 1st Shift or 2nd Sh	ft) Time: 5:00c	247
Unit	Visual Inspection <u>NORMAL</u> or ABNORMAL	Comments - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS

Visible Emission From Shaker

Conveyor System

Visible Emission From Discharge

VISIBLE EMISSION NOTATIONS				
Inspector:	Sincero			
Date of Inspection:				
10-7-12	<u> </u>			
Shift: 1st Shift or 2nd Shift	Time:			
		600pm		
Unit Control	Visual		Con	nments
	Inspection		and the second s	San Constitution
	<u>NORMAL</u>			or are profiled to

or ABNORMAL

Abrosma

NORmer

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Visible Emission From Shaker

Conveyor System

Visible Emission From Discharge







VISIBLE EMISSION NOTATIONS					
Inspector: Smello					
Date of Inspection:	5				
Shift: 1st Shift or 2nd Shift	Time:	JAM			
Adams the profit Unit Comparation of the Comparatio	Inspection. NORMAL		iec indones Nationaldien der Zoo 1994 in State State on State of Sooil 2004 in State of State of Sooil State of Sooil 2004 in State of State of Sooil State of Sooil	mments of the state of the stat	
	NORMAL FOR ABNORMAL				
Visible Emission From Shaker	noß		·		
Visible Emission From Discharge	000	<u> </u>			
Conveyor System	1108				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS Inspector:

Date of Inspection:

Shift: 1st Shift)

r 2nd Shift


Time:

5:00 pm

		3.00 pr.		
	Inspection NORMAL OI ABNORMAL		mments	
Visible Emission From Shaker	Nor		Na brimske regions visit and the first	
Visible Emission From Discharge	- A 7			
Conveyor System	Nor			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 5/1/2015



VISIBLE EMISSION NOTATIONS	C		_		
Inspector: Paul La	<u> </u>				
Date of Inspection:					
Shift: 1st Shift or 2nd Shift	Time:	5:00 AM			
Assemble of the County of the	Visual Inspections 15		Carrier and Authorization and	mmentse seelik	
	NORMAL or				
	<u>ABNORMAL</u>				
Visible Emission From Shaker	Nov				
Visible Emission From Discharge	100				
Conveyor System	1/101				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







AISIBLE EMISSION NOTATIONS						
Inspector: Charge A San	fu =					
Date of Inspection: /6/9/13					*	
Shift: 1st Shift or 2nd Shift	t Time:	5-60 pm				
Unit	Visual Visual Inspection 25			omments		
	<u>NORMAL</u>	producer (Constitution of Constitution of Cons	an characteristic Constitution and the energy of the constitution of the days of the constitution of the			
	<u>ABNORMAL</u>					
Visible Emission From Shaker	Nor					
Visible Emission From Discharge	12					
Conveyor System	NON					

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS					
Inspector: Smelko					
Date of Inspection:	(5				
Shift: 1st Shift or 2nd Shift	Time:	5 AM			
de para la compositio Direction de la composition della compositio	Inspection		Gomments:	Palainapatanise p <u>r</u> Palainapatanise production Palainapatanise production	on the five gas and the second
	NORMAL or ABNORMAL	The second secon			
Visible Emission From Shaker	nof	Section 1. The sectio			
Visible Emission From Discharge Conveyor System	nop				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTATIONS
Inspector: M. DHILLIPS
Date of Inspection:

2nd Shift Time: 1st Shift 5:00 pm.

			l			
	Silva Visuali William	near France Appellation (France) Progress (Prince Progress)		omments - Figure	enggangangan Kanggayan kanggar	a (Prophilippe) Service (Service)
	Inspection: NORMAL					
	or _{es} t to					
	ABNORMAL		生产的现在分词 医多种性			
Visible Emission From Shaker						
	MORMAL					
Visible Emission From Discharge						
Conveyor System	LIGHMAL	-				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

(Stack SDS 04)

VISIBLE EMIS	SSION NOTA	CIONS	5	
	1			

Visible Emission From Shaker

Conveyor System

Visible Emission From Discharge

Inspector: Jaime N Ga	a la company de		
Date of Inspection: 10/1/15			
Shift: 1st Shift (or 2nd Shift	Time: 5 pm		
Unit	Visual	Comments	
	Inspection	and the second of the second o	
	<u>NORMAL</u>		
	or, and a second of the second	The state of the s	
	ABNORMAL	and contract the first of the f	

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

(Stack SDS 04)

VISIBLE EMISSION NOTATIONS					
Inspector: Course A much	ecc				
Date of Inspection: 10/12/15					
Shift: 1st Shift or 2nd Shift	: Time:	5:00 pm			
Unit	Visual -	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	Com	nments :	
The second secon	Inspection				
	<u>NORMAL</u>		224 - 240 - 240		
	OF OUR STREET				
and the state of t	<u>ABNORMAL</u>	and the second s			
Visible Emission From Shaker	Nor				
Visible Emission From Discharge	ad 7				
Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS						
Inspector: Caurge A Sm	ncher					
Date of Inspection: 18/13/15				White you was a second of the		
Shift: 1st Shift or 2nd Shift	Time:	5:00 gen		***************************************		
Unit in the second of the seco	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments		930 (930) 300 (930) 300 (930) 300 (930) 300 (930)	
Visible Emission From Shaker	Nor					
Visible Emission From Discharge Conveyor System	Nor			- I was a second		

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

(Stack SDS 04)

٧	ISIBLE	EMISSION	NOTATIONS
---	--------	-----------------	-----------

Inspector: Smello				
Date of Inspection: 0 + 14	,15			
Shift: 1st Shift or 2nd Shift	Time:	SAM		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments:	
Visible Emission From Shaker	nor			!
Visible Emission From Discharge Conveyor System	nor			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS					
Inspector: George A San	whee				
Date of Inspection: 10/14/15					
Shift: 1st Shift or 2nd Shift	t Time:	5:00 pm			
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comr	ments	
Visible Emission From Shaker	Nor				
Visible Emission From Discharge Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.








VISIBLE EMISSION NOTATIONS			_		
Inspector: HURGY 1141	WANSTE				
Date of Inspection: V 5	%		VA		
Shift: 1st Shift or 2nd Shift	Time:	500AM	: : :		
Unit	Visual Inspection			Comments	
	NORMAL NORMAL				Merce estado de Maria de Carlos de C
	or <u>ABNORMAL</u>		100 (100 (100 (100 (100 (100 (100 (100	100 (100 (100 (100 (100 (100 (100 (100	
Visible Emission From Shaker	NOPMAL				
Visible Emission From Discharge Conveyor System	NORMAL				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS

VISIBLE LIVISSION NOTATIONS				
Inspector:				
Date of Inspection:				
Shift: 1st Shift or 2nd Shir	ft Time:			
The Unit was a second of the Control	Visual Inspection NORMAL Or ABNORMAL		nments a supplied the supplied to the supplied	
Visible Emission From Shaker	Dum			
Visible Emission From Discharge Conveyor System	Norn			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE	EMISSION	NOTATIO	N٩

Inspector:					
M. PHILL	1195				
Date of Inspection:					
10-16-1	<u> </u>				
Shift: 1st Shift or 2nd Shift	: Time:	•			
135 5HIET		5:00 pm.			
Unit	. Visual	A chapter than the	Comment	ts - I was in the same	
	Inspection				
	NORMAL			10 m	
	or or			Control of the Contro	ursa (california) alcohol
				Edial Control	2500
	ABNORMAL				
Visible Emission From Shaker					
	MERMAL				·
Visible Emission From Discharge				*	
Conveyor System	NORMAL				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS			_		
Inspector: Kuba	en Moder	d			
Date of Inspection:)-15				
Shift: 1st Shift or 2nd Shift	Time:	B:Car			
	Visual Inspection NORMAL or ABNORMAL		Commen	nts	
Visible Emission From Shaker	Norm				
Visible Emission From Discharge Conveyor System	Norm				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

(Stack SDS 04)


VISIBLE EMISSION NOTATIONS			_		
Inspector: Prome AS and	where				
Date of Inspection:					
Shift: 1st Shift or 2nd Shift	t Time:	\$100pm			
Unit	Visual Inspection	300 Sept. 100 Se	Comi	ments	
enter de la companya	<u>NORMAL</u>		A BANGARA A Marangaran Anggaran		
	or <u>ABNORMAL</u>				
Visible Emission From Shaker	Nor				
Visible Emission From Discharge					
Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector:	L			
Date of Inspection:				
Shift: 1st Shift or 2nd Shift	Time:	5.00 AW		
Unit and the second of the sec	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments	
Visible Emission From Shaker	Nor			·
Visible Emission From Discharge Conveyor System	nor			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.






VISIBLE EMISSION NOTATIONS

Inspector: Chevic	. S.		_		
Date of Inspection:	5		-		
Shift: Lst Shift or 2nd Shif	t Time:	530pm			
	Visual Inspection <u>NORMAL</u> or			Comments	
Visible Emission From Shaker	ABNORMAL ABA.	shaker b	oot needs	changing	
Visible Emission From Discharge Conveyor System	NOR.			0 0	

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS				
Inspector: Faul Lad				
Date of Inspection:				
Shift: 1st Shift or 2nd Shift	Time:	5:00 Am		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments Section 2015 Comments Comments Comments Comments Comments	
Visible Emission From Shaker	Not			·
Visible Emission From Discharge Conveyor System	505			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS			_		
Inspector: Saime N Coance	Va				
Date of Inspection: 0/19/19		·			
Shift: 1st Shift or 2nd Shift	Time:	5pm			
Appelled Control Control	AMERICAN DESCRIPTION OF THE PROPERTY OF THE PR				
	<u>NORMAL</u> OF				
	ABNORMAL - S				
Visible Emission From Shaker	NORMA			·	
Visible Emission From Discharge	61				
Conveyor System	/ Nacinal				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

(Stack SDS 04)

VISIBLE ENAISSION NOTATIONS			_			
Inspector: Hunn	loland					
Date of Inspection:	0-15					
Shift: 1st Shift or 2nd Shift	Time:	-				
Unit	Visual			Comments 👢 🔻	President State	
	Inspection				en e	
ng the second section of the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section in the second section is a second section of the second section is a second section in the second section is a second section in the second section is a second section of the second section is a second section in the second section in the second section is a second section in the second section in the second section is a second section in the second section in the second section is a second section in the second section in the second section is a second section in the second section in the second section is a second section in the second section in the second section is a section in the section in the section is a section in the section in the section in the section is a section in the section in the section is a section in the section in the section in the section is a section in the section in the section in the section is a section in the sec	<u>NORMAL</u>		e de como de la compansión			
	·= · or · ·					
	<u>ABNORMAL</u>					
Visible Emission From Shaker	Nom					
Visible Emission From Discharge	1 1000					
Conveyor System	VO14 2					

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS			<u> </u>	
Inspector: Dime N Gorce	ria			
Date of Inspection: 10/20/15				
Shift: 1st 8hift or 2nd Shift	Time:	5 pm		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comment	
Visible Emission From Shaker	Normal			,
Visible Emission From Discharge Conveyor System	Mormal			


- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	. 1				
Inspector: Huben	Moland				
Date of Inspection:	15	·			
Shift: 1st Shift or 2nd Shift	Time:)	5:00 anc			
Unit and a second secon	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Con	nments	
Visible Emission From Shaker	nomal				
Visible Emission From Discharge Conveyor System	Nomel				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.


AIZIBLE FIMIZZION NOTATIONS				
Inspector: Geogre A Jane	hez		,	
Date of Inspection:				
Shift: 2st Shift or 2nd Shift	t Time:	5-'00pm		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments Comments	
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.




Inspector:	Seremy Har	lôγ				
Date of Inspection:	10/22/15	-				
Shift: 1st Shift	or 2nd Shift	Time:	500am			
Unit	net la Tallación de la Carlo	Visual			Comments	
		Inspection.				esuper substitution
and the second second		NORMAL			ergen en Man	
		ABNORMAL		The state of the s	146 - 1977	
Visible Emission Fro	m Shaker	NORMAL				
Visible Emission Fro	m Discharge					
Conveyor System		Normal				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS Inspector: Date of Inspection: Shift: Time: Unit Visual Comments Inspection NORMAL or <u>ABNORMAL</u> Visible Emission From Shaker Wor Visible Emission From Discharge Nor Conveyor System


- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE	EMISSION	INOTATIONS
V 1310LL	LIVIIJJIOI.	

VISIBLE LIVIISSICIA NO DATIONS			_	
Inspector:	X			
Date of Inspection:	15			
Shift: 1st Shift or 2nd Shift	t Time:	5:00 Am		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments	
Visible Emission From Shaker	001			
Visible Emission From Discharge Conveyor System	No C			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



(Stack SDS 04)

Inspector: Garge ASA	neker					
Date of Inspection:	13		1			
Shift: 1st Shift or 2nd Shif	t Time:	5:00pm				
Unit	Visual				transfer (Line	
	Inspection					
The second secon	<u>NORMAL</u>					
$p_{ij}(a) = 2 \left(\frac{1}{2} \left(1$	or programme	1822 1 1 141 - War 192		1 (2 (2 (2 (2 (2 (2 (2 (2 (2 (2 (2 (2 (2	· 网络阿拉克斯	
	<u>ABNORMAL</u>			tige in the second	tal and the second second	
Visible Emission From Shaker	Nor					
Visible Emission From Discharge	11 /					
Conveyor System	1001					

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector: Vaul and				
Date of Inspection:	5			
Shift: 1st Shift or 2nd Shift	Time:	5,00 M		
Unit .	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		omments	
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	NOT			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS					
Inspector: Jaime 11 Gai	RC/a			÷	
Date of Inspection: 10/24/15					
Shift: 1st Shift or 2nd Shift	Time:	TPM			_
Unit	Visual Inspection <u>NORMAL</u> Or ABNORMAL		omments -		
Visible Emission From Shaker	Mormal				1 000 000 000 000
Visible Emission From Discharge Conveyor System	Normal				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS						
Inspector:	Moland					
Date of Inspection:	10-25-) 3				
Shift: 1st Shift or 2nd Shift	Time:	5:ccam				
Unit	Visual		Con	nments	entrope de la companya de la compan La companya de la co	
	Inspection'	and the second s				
The state of the s	<u>NORMAL</u>	direction of the second se				
	or			den de la company		
	<u>ABNORMAL</u>		en internacional de la companya de l	and the first of the second		
Visible Emission From Shaker	Norm					
Visible Emission From Discharge	W \					
Conveyor System	Nam					

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.








Inspector:			1		
\mathcal{M} .	25-15				
Date of Inspection:]		
10-	25-15]		
Shift: 1st Shift or 2nd Shift	: Time:				
	5	PM.			
Unit	Visual		Com	ments	er engliger i de Pije de Pijer i de Pijer i De pijer i de Pijer i
	Inspection		PERMITTEE STATE		
	<u>NORMAL</u>				
and the transport for the property of the second se	or		1000年1		
	<u>ABNORMAL</u>				
Visible Emission From Shaker					
	NORM.				
Visible Emission From Discharge					
Conveyor System	NORM!				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.




Inspector:				
Date of Inspection:				
Shift: 1st Shift or 2nd Shif	t Time:			
	Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	Normal			
Visible Emission From Discharge Conveyor System	Normal			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.


VISIBLE EMISSION NOTATIONS	·		_		
Inspector: George AS	unckez,				
Date of Inspection: 10/16/15					
Shift: 1st Shift or 2nd Shift	: Time:	5:00 pm			
Unit	Visual Inspection			Comments	and the second of the second o
	NORMAL				See 1
	or <u>ABNORMAL</u>				
Visible Emission From Shaker	Nor				
Visible Emission From Discharge	. 1				
Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.




Inspector: Smell(0)				
Date of Inspection:	5			
Shift: 1st Shift or 2nd Shift	Time: ,	5A.		
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments	
Visible Emission From Shaker	noR	-		
Visible Emission From Discharge Conveyor System	noR	mae'		

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.




Inspector: George AS	wehe z				
Date of Inspection:	5				
Shift: Ast Shift or 2nd Shift	Time:	STOOPM			
Unit	Visual	er e		Comments	
1 24 7 2 3 3 4 4 5 1 4 5 1 4 5 1 4 5 1 5 1 5 1 5 1 5	Inspection				
The second secon	<u>NORMAL</u>		Notice that the second		
and the state of t	or				
The state of the s	<u>ABNORMAL</u>	and the second second			
Visible Emission From Shaker	Nor				
Visible Emission From Discharge	.1				
Conveyor System	Nor				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VIOLETE ELITICOLOTI LES ILLIANO			<u> </u>		
Inspector: Smell6					
Date of Inspection: Oct AS	15				
Shift: 1st Shift or 2nd Shift	Time: ,_	JAM			
Unit	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>			ments	
Visible Emission From Shaker	Nor				
Visible Emission From Discharge Conveyor System	noR				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



Inspector: M. PHI	LIPS			
_ 	-8-15			
Shift: 1st Shift or 2nd Shift	t Time:	5 pm		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments Printing	
Visible Emission From Shaker	NORMAL	Georgia Champione		
Visible Emission From Discharge Conveyor System	NORMAZ			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.



(Stack SDS 04)

Inspector:				
Date of Inspection:				
Shift: 1st Shift or 2nd Shif	t Time:			
	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		Comments	
Visible Emission From Shaker	Namel			
Visible Emission From Discharge Conveyor System	Normal			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS		
Inspector: Jaime N Garria		
Date of Inspection: 10/19/18		
Shift: 1st Shift for 2nd Shift	Time: 6ph	
Unit	Visual	Comments

· Canada College	<u></u>	por		
Unit	Visual	Park Commence of the Commence	. Comments:	and the second s
particle to the plant of the particle of the p	Inspection			
	<u>NORMAL</u>			and the second s
2017年 - 13年 - 13日 - 13	or,			
	<u>ABNORMAL</u>			
Visible Emission From Shaker	Normal	Contraction designation of the Contraction of the C		
Visible Emission From Discharge	6/			
Conveyor System	Normal			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE	EMISSION	NOTA:	TIONS

Inspector: (MIMO N COCK	201a				•	
Date of Inspection: 10/30//3						
Shift: 1st Shift for 2nd Shift	t Time: 2	ppu				
Unit	Visual		ran en	omments 🖖 🔻		and the second s
And the state of t	Inspection	The state of the s	e de la Spelle			
For the second of the second o	<u>NORMAL</u>	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	r en tropical			
and the following the operator of the first section of the first section $(1/2)^{-1}$	or -		e de la participa de la composición de		1.0	
	ABNORMAL		area de la caractera de la composición	and the second		
Visible Emission From Shaker	Noemer (
Visible Emission From Discharge	11 /					
Conveyor System	1 VORMal					

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.





AISIBLE EMISSION MOTATIONS					
Inspector:	. Ula, y				
Date of Inspection:					
Shift: 1st Shift or 2nd Shift	Time:				
Unit	Visual Inspection <u>NORMAL</u> Or <u>ABNORMAL</u>		Com	ments	
Visible Emission From Shaker	Abramal	Charge So	rlen		
Visible Emission From Discharge Conveyor System	normal				

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS				
Inspector: George Asmer	he			
Date of Inspection: 10/31/15				
Shift: 1st Shift of 2nd Shift	Time:	5.'00 pm		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABNORMAL</u>		omments	
Visible Emission From Shaker	Nar			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the defree to which emissions reduce the transmission of light and obscure the view of an object in the background.